

Volcano Tag™



DURABLE LOW FREQUENCY RFID TAGS THAT PERFORM IN HIGH TEMPERATURE ENVIRONMENTS

- **High heat tolerance** – during storage, industrial processing, transportation and outdoor use
- **Durable housing** – withstands rigors of chemical and mechanical exposure
- **Versatile** – screw-mounts securely anywhere without compromising performance: glass, metal, plastic, or wood

Volcano Tag™ passive contactless radio frequency identification (RFID) transponders are built for reliable performance in high-heat conditions. For RFID applications where tags must perform before, amidst or following extreme heat exposure, Volcano Tag discs withstand peak temperatures up to 392° F (200° C).

Volcano Tag housings are composed of field-proven, temperature-stable polyphthalamide (PPA). This thermoplastic shell holds its shape despite high or fluctuating temperatures, protecting the electronics within. Exceptional toughness, chemical resistance and abrasion resistance assure consistent communications with RFID readers, and reliable performance in automation and manufacturing applications.

Low frequency (LF) Volcano Tag discs perform well affixed to virtually any surface – glass, metal, plastic or wood. They offer reliable, cost-effective tagging for near-proximity reader applications, with available data storage from a 64-bit user ID up to 264-bit read-write capability.

For additional disc-tag options, the HID Global IN Tag™ and Poly Tag families also include heavy-duty tags in low frequency, high frequency and UHF configurations. For lighter-duty applications, consider HID Epoxy Disc or World Tag™ RFID tags.

TECHNOLOGY HIGHLIGHTS:

- Peak temperature up to 392° F (200° C)
- Operating frequency 125 kHz
- Up to 264 EEPROM
- Waterproof
- Mount-ready, via central screw hole

APPLICATION AREAS:

- Automation and manufacturing
 - High temperature production processes
 - Machinery

SPECIFICATIONS



HID Global can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.

	Volcano Tag™	
	231	
Base Model Number	612170	601170
ELECTRONIC		
Operating Frequency	125 kHz	
Chip Type	Q5	Unique
Memory	264 bit EEPROM	64 bit read-only
Anti-Collision		
Reading Distance	Dependent upon reader, environment and application	
PHYSICAL		
Dimensions	Ø 1.02 x 0.16 in (Ø 26 x 4 mm)	
Mounting Method	Screw	
Fixation Hole Size	Ø 0.18 in (4.5 mm)	
Affixes To	Glass, metal, plastic, wood	
Housing Material	PPA	
Color	Black	
Weight	0.12 oz (3.5 g)	
CHEMICAL AND MECHANICAL		
Water	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h	
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]	
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]	
THERMAL		
Storage	-13° to +284° F (-25° to +140° C), 1000 h	
Operating	-13° to +185° F (-25° to +85° C)	
Shock/Fatigue	68° to +320° F (20° to +160° C), 100 x 5 min with 20 sec transition	
Peak	+320° F (+160° C) 1 x 100 h; 392° F (+200° C) 10 x 10 min	
OTHER		
Box Size	800 pcs	
Warranty	2 Years	



ASSA ABLOY

Microtron®

Flexible electronic solutions

Microtron n.v. | Generaal De Wittelaan 7 | B-2800 Mechelen | T +32 (0) 15 29 29 29 | info@microtron.be | www.microtron.be
 Microtron b.v. | Hoevestein 11 | NL-4903 SE Oosterhout | T +31 (0) 162 44 72 72 | info@microtron.nl | www.microtron.nl